

NOVA Executive desks



FEATURES

- Easy and fast assembling
- Easy to assemble and disassemble - "metal to metal" construction and fixings
- Just one tool for assembling (DIN911 S5)

QUALITY STANDARD

- LST EN 527-1:2011
- LST EN 527-2:2003
- All desks meet the requirements of the LST EN 527-3:2003 standard

TECHNICAL INFORMATION

Desktop

- 25 mm MFC (melamine) with 2 mm ABS edging;
- 25 mm chipboard covered in wood veneer with 2 mm edging;
- 10 mm gap between the legs and the desktop;
- Plain desktop or with a cut-out for grommet and wire management.

Legs

- Welded metal tube - 40x40 mm;
- Powder coated metal;
- Plastic feet with height levelling (+10 mm);
- Leg types - U or O.

Metal beam

- Metal tube - 40x20 mm;
- With welded metal plates for leg fixing;
- Powder coated metal, colour matches the legs.

GUARANTEE

- 5 years

MATERIALS


- Melamine: P (birch), T (beech), D1 (whitened oak), D2 (amber oak), U (walnut), M1 (white), N (grey), N1 (dark grey), M1D2 (white with amber oak edges);
- Veneer: K (maple), G (wenge), R (walnut);
- Metal: E (white), M (metallic), T1 (dark grey), A (black).

RANGE




ORDERING EXAMPLE

Code structure



Must be ordered

(for desktop with cut-out)




Metal grommet:
317x119 mm,
H=27 mm

Optional




Power socket
blocks



Cable trays




Cable clips



Cable ducts



CPU holders



Leather table
mats



Fixed pedestals



Pedestals